

ETCH GLASS

80µ TRANSLUCENT ETCH VINYL

Etch glass films ensure an elegant appeal in glass décor when a 'frosted' surface is required.

5/7
years



CAST PTCS Silver



PTAS Dark Silver



PTA Silver*



PTF Silver*



Face material:	80µ CAST vinyl (PTC series). Outdoor durability: 7 years**. 80µ polymeric vinyl (PTA/PTAS/PTF series). Outdoor durability: 5 years**.
Adhesive:	Permanent solvent acrylic featuring high cohesion and good water resistance.
Liner:	White kraft paper 135 g/m ² (PTC series) - 120 g/m ² (PTA/PTAS/PTF series*) that offers superior cuttability with conventional die-cutting and computer sign making systems.

OTHER PROPERTIES

Temperature range: Application: +10°C / +40°C; Operating: -20°C / +75°C.


Other Properties: Resistant to UV light, seawater, oils, hydrocarbons and gasoline. Flammability: Self Extinguishing.


Standard roll size: 1.22 m x 50 m (PTC series). 1.22 m or 1.52 m x 50 m (PTA/PTAS/PTF series).


*PTA and PTF are also available with Airflow technology


**Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.



	Frontale:	Film vinilico CAST 80µ (serie PTC). Durata in esterno: 7 anni**. Film vinilico polimerico 80µ (serie PTA/PTAS/PTF). Durata in esterno: 5 anni**.
	Adesivo:	Acrilico permanente a base solvente ad alta coesione e buona resistenza all'acqua.
	Supporto:	Carta kraft bianca 135 g/m ² (serie PTC) - 120 g/m ² (serie PTA/PTAS/PTF*) specificatamente studiata per taglio convenzionale e computerizzato.

	Obermaterial:	80µ CAST vinyl (PTC Serie). Haltbarkeit im Außenbereich: 7 Jahre**. 80µ Polymer-Vinyl (PTA/PTAS/PTF Serie). Haltbarkeit im Außenbereich: 5 Jahre**.
	Klebstoff:	Acrylat auf Lösungsmittelbasis, permanent haftend, mit hoher Kohäsion und ausgezeichnete Wasserbeständigkeit.
	Träger:	Weißes Kraftpapier 135 g/m ² (PTC Serie) - 120 g/m ² (PTA/PTAS/PTF Serie*) sehr gut geeignet zum konventionellen Stanzen und für CAD-/CAM-Anwendungen.

	Frontal:	Vinilo CAST 80µ (PTC serie). Durabilidad exterior: 7 años**. Vinilo polimérico 80µ (PTA/PTAS/PTF serie). Durabilidad exterior: 5 años**.
	Adhesivo:	Acrílico solvente permanente con alta cohesión y buena resistencia al agua.
	Soporte:	Carta kraft blanca estable 135 g/m ² (PTC serie) - 120 g/m ² (PTA/PTAS/PTF serie*) ideal para corte tradicional y asistido por ordenador.

	Frontal:	Vinyle CAST 80µ (série PTC). Durabilité extérieure: 7 ans**. Vinyle polymère 80µ (séries PTA/PTAS/PTF). Durabilité extérieure: 5 ans**.
	Adhésif:	Acrylique permanent à base solvant avec une haute cohésion et une excellente résistance à l'eau.
	Protecteur:	Papier kraft blanc 135 g/m ² (série PTC) - 120 g/m ² (série PTA/PTAS/PTF*) développé pour la découpe conventionnelle et assistée par ordinateur.

*PTA and PTF are also available with Airflow technology

**Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.