

## PRECAUTIONS FOR USE

Transparent cast film for the customisation and protection of tail lights that are **not certified for “on road” use**. This material has achieved the classification of reaction to fire B-S2-D0.



### WARNINGS FOR USE:

**TL/...:** full adhesive without air channels

**TL/...-FT:** adhesive with channels “Air Free FTX System”

**TL/...-FP:** adhesive with channels “Air Free FTX System. The material has a protective PET liner, to be removed prior to the application phase

Do not apply the film on surfaces that reach high temperatures for prolonged times (for example surfaces exposed to intense solar radiation or surfaces in contact with heat sources).

Once applied, where it has been conformed, it can be heated to **100°C** for definitive fixing.

During the cutting phase, to obtain a clean and precise cut of the film, always use a well sharpened cutter blade.

It is recommended to apply the film with the use of a felt applicator and to keep the cloth wet with water so as not to scratch the film.

Apply the film at a temperature between **15°** and **25°C** and only with dry method, except for films with full glue adhesive where the application must be carried out with the wet method, the use of AC.C2P8 is recommended.

The shine of the film highlights any scratch, mark or small imperfection on the surface; which is why any micro imperfections in the film cannot be considered as a defect.

The emission of gaseous substances released by some types of lights can cause premature aging and/or degradation of the self-adhesive film. In the event of visible alterations to the material, immediate removal is recommended.



## CLEANING THE FILM:

Use water with soft cloths and non-aggressive detergents. Do not use rough sponges and cloths, abrasive pastes, solvents.

Cleaning with unsuitable products and tools can cause premature degradation of the film. The surface of the film is very shiny and reflective therefore if mistreated it could irremediably become opaque and scratched.



## MAINTENANCE:

The surface of the film is delicate; therefore, it must be treated with care. Prolonged exposure to sunlight and atmospheric agents can cause premature aging of the film, especially of the parts exposed horizontally.

It is therefore advisable to protect the decorated surface, as much as possible, from the sun and atmospheric agents.



It is the responsibility of the purchaser and end user to comply with all laws and regulations concerning the use of light tinting films on vehicles and to assume any risks and responsibilities arising from such use. APA recommends for use on off road vehicles only (exhibition use).